



Type of drive : Elektrikli

Type of operation : Ayakta

Capacity : 1500 kg

Load center distance : 600 mm

Wheel base : 1231 mm

Service weight without battery : 390 kg

Service weight with battery : 440 kg

Wheel type : PU

Front wheel size : ø180 mm

Drive wheel size : ø210 mm

Tekerlek Sayısı : 4 adt
Lowered mast height : 2035 mm
Length with platform : 1718 mm
Rear body width : 830 mm
Height of tiller in drive position : 1310 mm
Rear body height : 850 mm
Mast extend height : 3500 mm
Lifting height : 3000 mm
Min. Ground clearance : 30 mm
Fork length : 1125 mm
Overall fork width : 560 mm
Turning radius : 1390 mm
Lowered height of fork : 90 mm
Fork thickness : 54 mm
Fork width : 160 mm
Fork tilting degree (forward/backward) : 2/5
Aisle width for pallets 800x1200 lengthways : 2184 mm
Aisle width for pallets 1000x1200 crosswaysr : 2256 mm
Traveling speed (with/without load) : 3.5 / 4 km/h
Lifting speed (with/without load) : 100/112 mm/sn
Lowering speed (with/without load) : 92/85 mm/sn
Gradient (with/without load) : 5/7 %
Driving motor : 0.65 kw
Lifting motor : 2.2 kw
Battery voltage/ capacity : 12/75x2 V/Ah
Battery size : (260x172x214)x2 mm
Brake type : Eletronik